



# DRUM PA-5K PRO

## ACCESSORIES



Two Rim mount clips for A-5t Tom Mics



Three Hard Mount Mic Clips



## SPECIFICATIONS

### A-55

Type	Dynamic
Frequency Response	30Hz - 15 kHz
Polar Pattern	Cardioid
Sensitivity	-76 dB (=/- 3 dB @ 1kHz)
Output Impedance	300 ohms
Size	60mm x 130mm
Weight	540g
Metal Finish	Black

### A-5t

Type	Dynamic
Frequency Response	50Hz - 18 kHz
Polar Pattern	Cardioid
Sensitivity	-76 dB re 1V/Pa
Output Impedance	600 ohms
Size	33mm x 85mm x 86.5mm
Metal Finish	Matte Black

### CR21

Type	Pressure Gradient Condenser Mic
Current Consumption	<3.0mA
Frequency Response	30Hz - 20 kHz
Polar Pattern	Cardioid
Sensitivity	10 mV/Pa
Output Impedance	200 ohms
Equivalent Noise	18 dB (A-weighted IEC 268-4)
S/N Ratio	80 dB (Ref. 1 Pa A-weighted)
Max SPL for .5% THD	134dB
Power Requirements	48V Phantom Power (+/- 4V)
Size	22mm x 135mm
Weight	130g
Metal Finish	Matte Black and Black Chrome

### 606

Type	Pressure Gradient Condenser Mic
Diaphragm	Gold-Splattered, 6 micron
Capsule Size	22mm/.87 in
Frequency Response	30Hz - 20 kHz
Polar Pattern	Cardioid
Sensitivity	15 mV/Pa
Output Impedance	150 ohms
Equivalent Noise	17 dB (A-weighted IEC 268-4)
S/N Ratio	77 dB (Ref. 1 Pa A-weighted)
Max SPL for .5% THD	137 dB
Power Requirements	48V Phantom Power (+/- 4V)
Size	110mm x 23mm/4.3 in. x 0.89 in
Weight	0.25 lbs/113g
Metal Finish	Silver