

# Marshall Electronics, Inc.

*Product Innovation Through Technical Excellence!*

1910 East Maple Ave. El Segundo, CA 90245

Phone: (310) 333-0606 Fax: (310) 333-0688 E-Mail: Sales@MXLmics.com

Internet: [www.MXLmics.com](http://www.MXLmics.com)

**Thank you** for purchasing an MXLV63M studio recording microphone. With proper care, this mic will provide many years of satisfaction. For best results, please take a few moments to review this literature.

## General Characteristics

This microphone has a one-inch gold sputtered diaphragm and a fairly wide fixed cardioid pickup pattern. Large capsule condensers are very sensitive, readily revealing very subtle sonic details. They also tend to pick up sounds outside the pattern more than some designs, which can lead to powerful feedback if you are not careful. We strongly advise experimentation with placement and isolation requirements with the gain initially set low to avoid equipment (and ear) damaging surprises!

## Power Requirements

**IMPORTANT** - This unit requires phantom power at 48 volts, +/- 4 volts. Each unit has been thoroughly checked before shipping, so if you hear no sound, check that the phantom power on your mixer or separate power supply is switched on!

## Isolation Mount

MXL57 Shock mount is available as an option.

## Microphone Cables


The microphone cable can have a profound effect on the sound of any microphone. Even the finest microphones will sound poor if the interconnect cable allows noise to enter, or causes distortion and loss of information. Use only the best microphone cable your budget will allow., we recommend Mogami Cable.

## Care

Dust and foreign material can degrade the performance of a microphone over time so always store the unit in its box. For vocals closer than 3", use a "**popper stopper**" or a foam windscreen to avoid getting moisture on the diaphragm as this can substantially degrade the microphone's performance.

## Data

Frequency Response	30Hz – 20 kHz
Polar pattern	Cardioid
Max SPL for .5 %THD	130 dB
Sensitivity	15 MV/pa
Output impedance	200 ohms
Equivalent noise	20db (A-weighted IEC 268-4)
Weight	470 g
Dimensions	55mm x 190 mm
Power Requirement	48 V phantom power (+/- 4 V)



## Warranty

The MXLV63M microphone is guaranteed against defects in material and workmanship for three years from date of purchase. Should you encounter any problem with this unit, promptly contact the store you purchased it from for assistance. The original dated sales receipt will be necessary for any warranty claim. Do not send any unit directly to us without prior authorization from our service department! Warranty coverage is limited to repair or replacement (at our option) of the microphone, and does not cover incidental damages due to use of this unit, nor damage caused by accidental misuse of this product.